THE WORLD LEADER IN FUME EXTRACTION TECHNOLOGY



BOFA's Advantage 200 Cooling Unit is an electrically driven, cooling air unit. It supplies cool, filtered air to both the laser and power supply module. This clean, cool air ensures optimal laser performance and reliability.

STANDARD FEATURES:

- Low noise level
- · Stainless steel unit
- Filter efficiency F7 (96% @ 2 microns)
- Filter condition indicator

OPTIONAL FEATURE:

HEPA filter

Filtered Cooling Unit. To ensure optimal performance and reliability.



| PART NUMBERS | | |
|-----------------|---------|----------|
| Model | Voltage | Part No. |
| AD 200 CU | 230V | L1152A |
| Stainless Steel | 115V | L1151A |

| REPLACEMENT FILTERS | | |
|---------------------|------------|----------------------|
| Model | Pre Filter | Optional HEPA Filter |
| AD 200 CU | A1030162 | A1030263 |

| ECHNICAL DATA | | |
|----------------------|--|--|
| | 230V | 115V |
| Dimensions (HxWxD) | 210 x 254 x 254mm | 8.3" x 10" x 10" |
| Cabinet Construction | Brushed stainless steel | Brushed stainless steel |
| Airflow / Pressure | 200m³/hr / 30mbar | 117cfm / 30mbar |
| Electrical Data | 230v 1ph 50/60Hz Full load current: 2 amps / 135watts | 115v 50/60Hz Full load current: 1.2 amps / 135watts |
| Noise Level | < 54dBA* | < 54dBA* |
| Weight | 5kg | 11lbs |

^{*} At typical operating speed.

| PRE FILTER SPECIFICATIONS | |
|---------------------------|----------------------|
| Filter Media | Glass Fibre |
| Filter Media Construction | 50mm Folded Pleat |
| Filter Efficiency | F7 (96% @ 2 microns) |

| OPTIONAL HEPA FILTER SPECIFICATIONS | |
|--|--|
| HEPA Filter Media | Glass Fibre |
| HEPA Media Construction | Maxi Pleat Construction with Webbing Spacers |
| Filter Efficiency | 99.997% @ 0.3 microns |


applications please call us for details. Replacement filters should always be ordered using the part number on the filters inside your

AIRFLOW THROUGH FILTERS Pre Filter Clean Air Contaminated Air

TECHNICAL SPECIFICATION

- 1 Unit/Filter Condition Light
- 2 On/Off Switch Power Inlet
- 3 Filter Compartment Latch

- 4 Motor Cooling In & Out
- 5 Hose Inlet Connection 75mm
- 6 Air Inlet



British Quality



BOFA INTERNATIONAL LTD









